

Diesel Generator Katolight - MTU 60 KW

\$ Call (800) 248-8070

Model: **DS00060D6S-AK0574**
Engine Model: **John Deere 5030HF285,**

RATINGS -

Single Phase (Can be converted to 3 Phase)
KW: 60,
KVA: 60,
P.F.: 1,
Temperature Rise:
Voltage: 240 Volt 1 Phase 12w 60Hz
Temperature Rise: 130 Deg,
COOLING SYSTEM: 50 Deg C Cooling System,

CONTROL PANEL

45K Control Panel,
Emergency Stop Button,
Unit Mounted LH Side,

CIRCUIT BREAKER

Circuit Breaker Rating - CB 80% Rated
250 Amp J Frame 2 Pole 80% Standard CB,
Mounting Instructions: Circuit Breaker Factory Installed RH Side,
- Note: All breaker accessories are wired to a terminal strip for customer connection.

OTHER COMPONENTS

Jacket Water Heater:
-20 Deg F Block Heater 120V 1PH - 1500W,
Jacket Water Heater Mounting Instructions:
Jacket Water Heater Accessories: Isolation Valves (2),
Air Filter: Standard Duty,
Crankcase Vent System: No Crankcase Ventilation Filter (Standard),
Battery Configuration: Battery; Rack & Acid,
Battery Charger: GUEST 12-6A,
Battery Charger Mounted and DC Wired,

PAINT:

Paint Color Selected: Tan

HOUSING

Housing Option: Level 1 Enclosure -
Enclosure Type: Level 1 - Steel,
- Wind Rating 150 MPH
Exhaust Grade: Hospital Grade Silencer

FUEL TANK

No Fuel Tank

MISC

WARRANTY

Warranty Selected: 2 Yr/3000 Hr Basic Stdby Limited Warranty



Photo may not be actual unit listed.



Photo may not be actual unit listed.