



Unloading Equipment



High Capacity

Sweepway™ - The Fastest, E



Augers are dangerous. Individuals should never enter a grain bin while the bin is being loaded or unloaded. Follow all applicable safety regulations.

The Sweepway™ is the ultimate bin unloading system.

- The unloading sweep is permanently installed in the bin for easy operation. No heavy sweep and motor to carry in and out.
- The Sweepway™ saves time and labor. There's no need to enter the bin; the Sweepway™ advances into the grain, removing it without back-breaking scooping.
- Special design prevents opening the intermediate sumps without opening the center sump to protect the sidewalls from uneven unloading.
- Split backboard on units larger than 60' reduces sidewall stress during unloading.
- Intermediate sumps are welded to the unload tube at the factory, so there's no assembly necessary.
- Number of intermediate sumps is predetermined based upon bin diameter - up to six sumps are used.
- Optional band-on independent sump can be used to unload bin without stressing sidewalls if center sump is blocked. It is three times larger than standard intermediate sumps!



Just one pass and the Sweepway™ Power Sweep will clean up.

Galvanized Backboard

The Sweepway™ Power Sweep is equipped with a galvanized backboard that keeps the sweep close to the floor as it propels itself around the bin. The tall galvanized backboard prevents grain flow over the top.

Patented, Adjustable Scrapers

A galvanized scraper is attached to the backboard to ensure that the most grain possible is picked up off the floor. The scraper is adjustable to different heights to meet your needs.

(U.S. Patent #6,254,329)



Exclusive Reduction Drive

Exclusive reduction drive, standard on all Sweepway™ Power Sweeps, decreases drive wheel speed without sacrificing forward movement. The auger turns four times to every one turn of the wheel. With this lower speed, wheel slippage is reduced and wheel life is prolonged.



Exclusive Carrier Wheels

Sukup sweeps for 40' diameter bins and larger feature a carrier wheel mounted to the back side of the backboard to keep the sweep running level. Backboards for bins larger than 48' diameter feature a patented carrier wheel that is in line with the auger to improve forward movement without interfering with grain discharge.



U.S. Patent #6,948,902




Unloading Capacities*

	6"	8"	10"
Horizontal	1500 bu/hr	2600 bu/hr	4000 bu/hr
Vertical	1250 bu/hr	2500 bu/hr	3750 bu/hr
Incline	1000 bu/hr	2000 bu/hr	3400 bu/hr

*Capacities are for Sweepway and Tube and Well Systems during gravity unload.

ty Bin Unloading

Easiest Way to Unload Grain



The unique design of Sweepway's center sump increases unloading capacities and ensures trouble-free operation.

- Upper and lower gearboxes are offset to provide a larger opening for grain to flow.
- Unload flighting extends past bin center to maximize capacity.
- Heavy-duty external clutch enables the unload auger to operate without the power sweep, so you can unload with gravity before engaging the power sweep.
- Sukup manufactures and assembles the gearbox and center sump to ensure top quality.



Shields removed to show detail. Keep shields in place.

- 8" & 10" sumps have a larger bearing mount that is 1-1/2 times stronger than previous designs and a thicker bearing housing for greater durability.
- Self-cleaning center sump and slide gates allow you to control the flow of grain from the bin.
- 8" center sump is 1-1/2 times larger than a traditional 8" center sump for better grain flow.
- Sealed roller bearings (std) make it easier for center slide gate to move under pressure from even high grain depths. 8" and 10" intermediate sumps also have sealed roller bearings.

System Size	Floor Clearance*
6"	12"
8"	13 1/4"
10"	13 1/4"

* Required clearance is measured top of floor to concrete.

Sukup Sweepways™ are built to last.

Sukup uses 7 gauge flighting on 6" and 8" Sweepway™ unload augers and 1/4" flighting on 10" Sweepways. This means you're getting commercial-grade strength and durability in each and every unit.

Safer - No need to enter bin.

- All controls are located on the outside of the bin, so there's no reason to enter the bin while augers are running.

- All 8" and 10" Sweepway powerheads are equipped with a rack and pinion sump opener.



Rack & Pinion Opener

- All 6" Sweepways are equipped with a specially-designed opener that provides extra leverage for opening sumps even under deeper grain.

- The exclusive sweep stop may be swung out from the wall to stop the sweep after one pass around the bin. Flip the sweep stop back and the bin is ready to fill.



Sweep Stop

- Optional Grain Buster breaks up grain clumps around the center sump that block the flow of grain. This simple, unique system is completely operated from outside the bin, eliminating the need to enter the bin.



Grain Buster Option

Solutions™

Simple, Rock-Solid Powerheads for Sweepway™ or Tube & Well Systems

Easy Belt Adjustments

The powerhead design for both the Sweepway™ and Tube & Well systems makes belt adjustments easier. A hinge on all powerheads allows the belt to be tightened by simply turning one 3/4" bolt. By removing the hinge pin, the motor may be easily moved to another bin.



Better Serviceability

Why remove the powerhead to service the flighting on your unloading equipment? You don't have to with Sukup powerheads or vertical augers. Sukup's special design allows you to pull the flighting without removing the powerhead, so Sukup units are much easier to service.



In addition, Sukup unload augers attach to the gearbox with a square shaft, rather than bolting to it. This arrangement makes it possible to remove the auger from the gearbox and continue unloading, if necessary. The tapered end makes it easier to connect the shaft to the auger.



Sukup Vertical Augers provide the highest unloading capacities in the industry.

- Available in 6" or 8" diameters, top or bottom drive, 16' or 20' heights. 10" available in 16' height.
- Double flighting at the bottom of the vertical auger picks up grain from the unload tube faster to increase capacity without the necessity of using a larger diameter vertical tube.
- Vertical auger turns faster than the horizontal unload auger to move grain up and out more quickly.
- Special boot design provides unrestricted grain flow from the horizontal unload tube into the vertical.



Galvanized Incline Augers

- 5', 25° incline on 6" or 8" systems; 7', 20° incline on 10" systems.
- Goes from 6" to 8" on 6" systems, 8" to 10" on 8" systems, and 10" to 12" on 10" systems.
- Heavy-duty universal joint with support bushing.
- 6" or 8" inclines attach to bin with two chains. Optional support legs are also available.



10" incline auger shown with optional support leg.



Drive Options for Sukup Sweepway™ and Tube & Well Unloading Systems



Single Motor
Horizontal Drive



Single Motor
Vertical Drive



Two Motor Vertical
Drive - Top or Bottom

Also Available:
8" Power-Take-Off
Horizontal Drive

Shields removed to show detail. Always keep shields in place.

Tube & Well



Low Cost ■ Easy to Service ■ Move from One Bin to Another

Sweep can be moved from bin to bin.


With the Sukup carry-in sweep, you can move the entire unit from one bin to another in no time.

- The Sukup carry-in sweep includes the drive belt, galvanized backboard with patented sweep scrapers, and direct drive wheel.
- Reduction drive wheel, as shown on the Sweepway™, is an option on all 6" and 8" carry-in sweeps up to 40'.
- Reduction drive is standard on 8" carry-in sweeps over 40' and all 10" carry-in sweeps.



Center Sumps

- 6" and 8" galvanized center sumps are available in full gate or concrete (half-gate) style.
- 10" center sumps are full gate style only. 10" sumps fit under 13 1/4" supports.



Choose Angle Ring or Sleeve Mount

- 6" and 8" Sukup Tube & Well systems are available as either angle ring or sleeve mount units.
- 10" systems are available as sleeve mount only.
- Angle ring units are compatible with other brands of equipment and feature 24" of stub flighting in the powerhead.
- Sleeve mount units feature one piece flighting.
- Roller bearings are standard on 10" center sumps. Roller bearings or nylon slide rails optional on 6" and 8" center sumps.



Intermediate Sumps

- Intermediate sumps are band-on, half gate type
- Optional rollers are available for 6" and 8".
- Control rods on 6" and 8" are telescoping, center pull type.
- Rods are located on both sides of the tube on 10" systems.
- The intermediate sump top is separate from the sump for easy installation.

Tube & Well Specifications				
CAPACITY*	6"	8"	10"	12"
w/horizontal	1500 Bu/Hr	2600 Bu/Hr	4000 Bu/Hr	6000 Bu/Hr
w/vertical	1250 Bu/Hr	2500 Bu/Hr	3750 Bu/Hr	-
SLEEVE MOUNT				
Unload Flighting	one piece	one piece	one piece	
Shaft & bearing dia	1"	1 1/4"	2" sh., 1 1/4" b.	not available
Flighting Gauge	11	11	7	
Unload Tube	14 ga. painted or galvanized	14 ga. painted or galvanized	12 ga. galvanized	
ANGLE RING				
Unload Flighting	used w/stub flighting	used w/stub flighting	not available	used w/stub flighting
Shaft & bearing Dia	1"	1 1/4"		2 1/2"
Flighting gauge	11	11		1 1/4"

*Capacities are for Sweepway and Tube and Well Systems during gravity unload.

Upgrade Your System

No Matter How Big Your Operation, Sukup Has the Equipment You Need.

Along with the full line of bin unloading equipment, Sukup also manufactures a complete line of bins and dryers for on-farm and commercial drying and storage.

Sukup Bins are available in sizes up to 135' diameter, with holding capacities up to 1.2M bushels.



Drag Conveyors

- 909, 1209, 1609 and 2109 Sukup Drag Conveyors fit under standard bin floors.
- Up to 6200 bu/hr. capacity
- All galvanized construction for long life.
- Turned, ground and polished shafts for smooth operation.
- Entire bearing, sprocket and shaft assembly can be removed without having to separate the components.
- Chains are engineered for each specific unit and are either roller bushed or welded steel.
- UHMW paddles, 1/2" thick, eliminate steel-to-steel contact.



Transfer, Utility and Roof Augers

Sukup transfer, utility and roof augers are just what you need to complete your bin system.

- Transfer augers
 - 20' lengths
 - 6" or 8" diameters



- Utility augers
 - 10', 15', or 20' lengths
 - 4", 6", 8" or 10" diameters
- Roof-Mounted Augers
 - 14', 20', 24' or 28' lengths
 - 8" or 10" diameters



Sukup Manufacturing Company ■ www.sukup.com

Box 677 ■ 1555 255th St. ■ Sheffield, IA 50475-0677 ■ Phone: 641-892-4222

Fax: 641-892-4629 ■ Email: info@sukup.com

Distribution Arcola, IL 61910
Centers 980 E. State Rd.
Located in: 217-268-3026

Aurora, NE 68818
1705 Hwy. 34 E.
402-694-5922

Defiance, OH 43512
7724 Rte. 66 N
419-784-9871

Jonesboro, AR 72403
5917 E. Johnson Ave.
870-932-7547

Cameron, MO 64429
7426 NE 352nd St.
816-649-2226

Watertown, SD 57201
2701 Piper Ave.
605-882-6697